**Last name** _____

**First name** _____

**LARSON—MATH 591–SAGE WORKSHEET 02**
**Sage Basics.**

1. (a) Start Firefox or Chrome browser.
   (b) Go to `http://cloud.sagemath.com`
   (c) Click "Sign In".
   (d) Click project **Math 591**.
   (e) Click "New", call it **s02**, then click "Sage Worksheet".

2. A very useful arithmetic operator in Sage is the *modulo* operator (represented by %). `a%n` gives the remainder of dividing $a$ by $n$. Evaluate `5%2`. Now evaluate `6%2`. Try `99%5`.

**Boolean Expressions in Sage**

A *boolean expression* is one that evaluates to True or False.

3. Evaluate `3==4`.

4. Evaluate `3==3`.

5. Evaluate `3>3`.

6. Evaluate `3>=-3`.

7. Evaluate `13%2==1`.

8. Evaluate `13%2==0`.

While "==" is used as a claim of equality of expressions (the left-hand-side and the right-hand-sides of the "==") the symbol "!=" is used to express does-not-equal.

9. Evaluate `5!=7`.

10. Evaluate `5!=5`.

11. We will *assign* a value to a variable "a". Then we will use that variable in a boolean expression. (These two lines can be typed in one cell, or each in its own cell). Type and evaluate:

```
a=5
a>2
```

Boolean expressions can be combined with *boolean operators* like "and" and "or".

12. Evaluate `3==3 and 3==4`.

13. Evaluate `3==3 or 3==4`.

**Lists in Sage**

A *list* is a basic *data structure* in Python and Sage. They are represented by square brackets with comma separated numbers, strings, etc., between them (like $[2, 5, 9]$ or `["red", "blue"]`).

14. Lists can be given names. Evaluate `L=[2,5,9]`. Then evaluate `L`.

15. Lists are indexed starting with 0. Evaluate each of `L[0]`, `L[1]`, `L[2]`, and `L[3]`.

16. Lists can be combined with "+". Evaluate `[2,5,9]+[3,4,5]`.

17. Let `M=[3,4,5]`. Evaluate `L+M`.

18. If you want all the integers from $x$ to $y$ you can use the shorthand notation $[x..y]$. Evaluate `[3..7]`.

19. If you want a list with $m$ $n$'s you can use the shorthand notation $[n] * m$. Evaluate `[0]*7`.

20. You can have a list of lists. Evaluate `L=[[0,1],[2,3],[4,5]]`. Now evaluate `L[1]`. Then evaluate `L[1][0]`. What do you think the value of `L[0][1]` is?

21. You can use `map()` to apply a function to each term of a list. Evaluate `map(x**2,[2,5,9])`.

22. What could you write to produce a *list* of all the cubes of the integers from 2 to 17?